

## 1800F Multi-Conductor - Single-Pair Cable



For more Information  
please call

1-800-Belden1

**Description:**

24 AWG stranded (42x40) HC BC conductors, Datalene® insulation, conductors cabled with fillers, TC "French Braid" Shield (95% coverage), BC drain wire, PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

# Pairs	AWG	Stranding	Conductor Material	Dia. (mm)
1	24	42x40	BC - Bare Copper	0.6096

**Insulation****Insulation Material:**

Insulation Trade Name	Insulation Material	Dia. (mm)
Datalene®	FHDPE - Foam High Density Polyethylene	1.4732

**Outer Shield****Outer Shield Material:**

Type	Outer Shield Material	Coverage (%)
French Braid	TC - Tinned Copper	95

**Outer Shield Drain Wire AWG:**

AWG	Stranding	Drain Wire Conductor Material
26	Stranded	BC - Bare Copper

**Outer Jacket****Outer Jacket Material:**

Outer Jacket Material
PVC - Polyvinyl Chloride

**Overall Cabling**

Overall Nominal Diameter: 5.359 mm

**Pair****Pair Color Code Chart:**

Number	Color
1	Red & Black

**Mechanical Characteristics (Overall)**

Operating Temperature Range:	-20°C To +60°C
Non-UL Temperature Rating:	60°C
Bulk Cable Weight:	35.717 Kg/Km
Max. Recommended Pulling Tension:	184.600 N
Min. Bend Radius (Install)/Minor Axis:	57.150 mm

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CL2R
EU CE Mark:	Yes

## 1800F Multi-Conductor - Single-Pair Cable

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MIL Order #39 (China RoHS):	Yes
Other Specification:	AES/EBU Digital Audio

## Flame Test

UL Flame Test:	UL1666 Riser
----------------	--------------

## Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

## Electrical Characteristics (Overall)

## Nom. Characteristic Impedance:

Impedance (Ohm)

110

## Nom. Inductance:

Inductance (µH/m)

0.59058

## Nom. Capacitance Conductor to Conductor:

Capacitance (pF/m)

39.372

## Nom. Capacitance Cond. to Other Conductor &amp; Shield:

Capacitance (pF/m)

85.306

## Nominal Velocity of Propagation:

VP (%)

76

## Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/km)

77.7597

## Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/km)

21.064

## Nom. Attenuation:

Freq. (MHz) Attenuation (dB/100m)

.384 1.50926

.706 2.19827

.768 2.2967

1.024 2.72323

1.411 3.41224

1.536 3.57629

2.048 4.2653

2.822 5.44646

3.072 5.74175

4.096 7.31663

5.645 9.48209

6.144 10.0727

8.192 12.1725

11.290 14.8629

12.288 15.6832

## 1800F Multi-Conductor - Single-Pair Cable

24.576	23.3279
--------	---------

**Max. Operating Voltage - UL:**

<b>Voltage</b>
300 V RMS

**Max. Recommended Current:**

<b>Current</b>
2.75 Amps per conductor @ 25°C

**Notes (Overall)**

**Notes:** Datalene® insulation features include low dielectric constant and a dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
1800F B59U1000	305 MT	11.793 KG	BLACK, MATTE		#24 PR FHDPE BRD PVC
1800F B591000	305 MT	10.886 KG	BLACK, MATTE	C	#24 PR FHDPE BRD PVC
1800F B59500	152 MT	5.443 KG	BLACK, MATTE	C	#24 PR FHDPE BRD PVC
1800F G7VU1000	305 MT	11.793 KG	RED, MATTE		#24 PR FHDPE BRD PVC
1800F G7WU1000	305 MT	11.793 KG	GREEN, MATTE		#24 PR FHDPE BRD PVC
1800F G7XU1000	305 MT	11.793 KG	BLUE, MATTE		#24 PR FHDPE BRD PVC
1800F G8MU1000	305 MT	11.793 KG	YELLOW, MATTE		#24 PR FHDPE BRD PVC
1800F U90U1000	305 MT	11.793 KG	GRAY, MATTE		#24 PR FHDPE BRD PVC

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 1    Revision Date: 05-14-2007

© 2008 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.